


Calido Clickbeam Mini

742129.002.1 | Surface mounted projector

Surface mounted projectors
4051859364351
LED
D 50, H 132



LED surface-mounted projector with modern cylindrical design with no visible cooling ribs. Housing: extruded aluminium profile, powder-coated. Cover and lever arm made of plastic. Rotation range: 356°. Swivel range: 90°. Heat resistant plastic ring black. Hybrid optical system with polycarbonate lens and reflector in faceted aluminium for particularly homogeneous lighting. Special Click Beam lens suitable for different beam angles. Adjustable lens position by means of push mechanism to adjust the beam angle. Black front ring to prevent glare from the side. UVA- and IR-free light. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. Converter integrated in the luminaire housing. The following accessories can be mounted without use of tools: honeycomb louvre.

Colour

Colour Traffic white, matt (RAL 9016)

Dimensions

Diameter D 50 mm
Height H 132 mm
Weight 180 g

Lamp

Lamp LED
Colour temperature 4000K
Colour rendering index (CRI) 80
Colour tolerance 3
Rated life 25000 h (L70/B50)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 1.300 lm
Glare evaluation UGR (4H 8H) 1 19,4
Beam angle 21°
Colour temperature 2 4.000 K
Rated luminous flux 2 1.250 lm
Glare evaluation UGR (4H 8H) 2 20,3
Beam angle Down 2 34°

Electrical

Control gear Converter
Voltage 220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse 11
Luminaires on B16A fuse 18
Luminaires on C10A fuse 22
Luminaires on C16A fuse 36
Inrush current / Inrush current duration 4.38 A / 24 µs
System power 12 W
Luminaire efficacy 109 lm/W
System power 2 12 W
Luminous efficiency 2 105 lm/W
Power factor 0,9

Approbations

Type of protection IP 20
Protection class II
Filament test 850°C - 30 seconds
Impact resistance IK03 (0,35 Joule)
Safety marks F-mark
ULOR 0
Conformity mark CE, EAC
CIE Flux Code / CEN Flux Code 94 99 100 100 100
Energieeffizienzklasse 2019/2015 D

Calido Clickbeam Mini

742129.002.1 | Surface mounted projector



Accessories

982448.003

Anti-glare honeycomb louvre
D 47, H 4
Anti-glare honeycomb louvre
Calido Mini