



# Levido Swing Round

901608.002 | Recessed projectors

Recessed projectors  
4051859157281  
LED  
D 91, H 2, HEL 92



Recessed projector with very small dimensions. Die-cast aluminium cover, powder-coated. Extruded aluminium heat sink. Reflector: aluminium, highly polished anodised finish. With safety glass. Can be swivelled by  $\pm 25^\circ$ . Suitable for Recessed ceiling mounting. Luminaire mounting with spring system. Incl. separate LED converter with connecting cable 250 mm. Opal PMMA plastic cover included as accessory.

## Colour

Colour white

## Dimensions

Diameter D 91 mm  
Height H 2 mm  
Cut-out diameter DA 78 mm  
Recess height HE 95 mm  
Luminaire: recess height HEL 92 mm  
Ceiling thickness S 1-20 mm  
Dimensions L 107 x B 36 x H 25 mm  
Weight 320 g

## Lamp

Lamp 1 LED  
Colour temperature lamp 1 3000K  
Colour rendering index (CRI) 1 80  
Colour consistency (McAdam) 1 4  
Lifetime of lamp 1 combined 50000 h (L70/B10)  
Photobiological safety according to EN 62471 Risk group 1

## Lighting technology

Colour temperature 3.000 K  
Rated luminous flux 920 lm  
Glare evaluation UGR (4H 8H) 1 25,8  
Beam angle 43°

## Electrical

Control gear Converter  
Voltage 220 - 240 V / 50 - 60 Hz  
System power 13 W  
Luminaire efficacy 71 lm/W  
Power factor 0,9

## Approbations

Type of Protection IP 20, IP 40  
Protection Class II  
Glow Wire Test 850°C - 30 seconds  
Impact Protection IK06 (1 Joule)  
Safety marks Einbauleuchte nicht bedecken!, F-mark  
ULOR 0  
Trade mark CE, EAC  
CIE Flux Code / CEN Flux Code 90 95 99 100 100  
Energy efficiency class LED A+  
Energy class of included lamp A+