



Less is more 21

312227.002.1 | LED linear systems

Pendant luminaires
4051859234234
LED
L 1208, B 21, H 36



Minimalist pendant luminaire with light emission on three sides. Housing: extruded aluminium profile, anodised or powder-coated. End cap anodised aluminium or powder-coated. Diffuser: plastic (non-yellowing PMMA), opal. Suitable for Pendant. 2-point steel cable suspension, steplessly adjustable. Special lengths available on request. Converter integrated in the canopy.

Colour

Colour white

Dimensions

Length L 1.208 mm
Width B 21 mm
Height H 36 mm
Suspension length 100-1500 mm
Weight 1,31 kg

Lamp

Lamp 1 LED
Colour temperature lamp 1 4000K
Colour rendering index (CRI) 1 80
Colour consistency (McAdam) 1 3
Lifetime of lamp 1 combined 60000 h (L80/B10)
Photobiological safety according to EN 62471 Risk group 1

Lighting technology

Colour temperature 4.000 K
Rated luminous flux 2.050 lm
Glare evaluation UGR (4H 8H) 1 25,4
Beam angle 180° / 115°

Electrical

Control gear	Constant voltage supply
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	14
Luminaires on B16A fuse	22
Luminaires on C10A fuse	23
Luminaires on C16A fuse	37
Inrush current / inrush current duration	23.5 A / 240 µs
System power	20 W
Luminaire efficacy	103 lm/W
Power factor	0,5

Approbations

Type of Protection	IP 20
Protection Class	I
Glow Wire Test	650°C - 30 seconds
Test marks	ENEC, VDE
Safety marks	F-mark
ULOR	28 %
Trade mark	CE
CIE Flux Code / CEN Flux Code	33 62 84 72 100
Energy efficiency class LED	A++
Energy class of included lamp	A++