



- Aluminium profile body.
- Plastic end caps.
- Mains voltage: 220-240V / 50-60Hz.
- Clever thermal design.
- 1-10V and DALI dimming options available upon request.
- Opal diffuser and alternatively clear diffuser options available.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- Up to 75lm/W efficiency.
- Tilttable light heads.
- Emergency kit system can be integrated.

- Alüminyum profil gövde.
- Plastik kapak.
- 220-240V / 50-60Hz enerji girişi.
- Akıllı soğutma tasarımı.
- 1-10V ve DALI dim seçenekleri bulunmaktadır.
- Opal diffüzörlü ve alternatif olarak şeffaf difüzör seçeneği mevcuttur.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe bağlı özel renk seçenekleri mevcuttur.
- 75lm/W'a kadar verim.
- Yönlendirilebilir ışık gövdesi.
- Acil aydınlatma kit sistemi uygulanabilir.

Rood / I02.LL.19210

SMD LED	.28	.37	.46
Led Power / Led Gücü	26W	34W	43W
System Power / Sistem Gücü	28W	37W	46W
Lumen Output from Fixture / Armatür Çıkışı Lümeni CRI>80	2700K	1875	2500
	3000K	1932	2575
	3500K	1990	2650
	4000K	2050	2730
	5000K	2110	2800
Lenght / Uzunluk (A)	900mm	1180mm	1460mm
Ceiling Cutout Dimension / Tavan Delik Ölçüsü	X	X	X
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	X	X	X
1-10V Dimming Option / 1-10V Dim Seçeneği	✓	✓	✓
Dali Dimming Option / Dali Dim Seçeneği	✓	✓	✓

Suspension Cord

Ray Sarkıtma Teli

