


TX-Move

742164.002.1 | Surface mounted projector

Surface mounted projectors
4051859755746
LED
L 569, B 119, H 75



Dreh-/Schwenkbarer Anbaustrahler in sehr flacher Bauform. Gehäuse Stahlblech pulverbeschichtet. 356° horizontal dreh- und zweimal 90° vertikal schwenkbar. Consistent alignment possible with visible tilt scale. High-efficiency LED units with flush-mounted opal diffuser made of non-yellowing PMMA. Symmetrical wide beam light emission. With multi adaptor for 3-circuit tracks 230 V. Suitable for Track on ceiling. MultiLumen-Funktion über Jumper mit drei Leistungsstufen.

Lighting technology

Colour temperature	4.000 K
Rated luminous flux	5.250 lm
Glare evaluation UGR (4H 8H) 1	28,2
Beam angle	111°
Colour temperature 2	4.000 K
Rated luminous flux 2	7.150 lm
Glare evaluation UGR (4H 8H) 2	29,3
Colour temperature 3	4.000 K
Beam angle Down 2	111°
Rated luminous flux 3	8.750 lm
Glare evaluation UGR (4H 8H) 3	30
Beam angle Down 3	111°

Colour

Colour Traffic white, matt (RAL 9016)

Dimensions

Length L	569 mm
Width B	119 mm
Height H	75 mm
Weight	2,1 kg

Lamp

Lamp	LED
Colour temperature	4000K
Colour rendering index (CRI)	80
Colour tolerance	3
Rated life	50000 h (L80/B10)
Photobiological safety according to EN 62471	Risk group 1

Electrical

Control gear	Converter
Voltage	220 - 240 V / 50 - 60 Hz
Luminaires on B10A fuse	15
Luminaires on B16A fuse	24
Luminaires on C10A fuse	24
Luminaires on C16A fuse	40
Inrush current / Inrush current duration	21 A / 220 µs
Ripple current / Flicker	4 %
System power	41 W
Luminaire efficacy	129 lm/W
System power 2	57 W
Total harmonic distortion	20 %
Luminous efficiency 2	126 lm/W
Power factor	0,9
System power 3	73 W
Luminous efficiency 3	120 lm/W

TX-Move

742164.002.1 | Surface mounted projector



Approbations

Type of protection	IP 20
Protection class	I
Filament test	650°C - 30 seconds
Impact resistance	IK03 (0,35 Joule)
Safety marks	F-mark
Ambient temperature min.	5 °C
Ambient temperature max.	25 °C
ULOR	0
Conformity mark	CE
CIE Flux Code / CEN Flux Code	47 79 96 100 100
Energieeffizienzklasse 2019/2015	C
Non-maintained power mode	Umgebungstemperatur / temperature ambiante => 5 °C ... + 25 °C