



- Aluminium body.
- Microprismatic PMMA opal diffuser.
- Mains voltage: 220-240V / 50-60Hz.
- 1-10V, DALI and switch dimming options available upon request.
- Over 100lm/W efficiency.
- Emergency kit system can be integrated.
- Basic colours: white, black, silver, antracite dark gray and special color options available upon request.
- Electronic Led driver built in inside luminaire.
- Steel suspension chain up to 5mt lenght.

- Alüminyum gövde.
- Mikroprizmatik PMMA opal difüzörlü.
- 220-240V / 50-60Hz enerji giriřli.
- 1-10V, DALI ve switch dim seçenekleri bulunmaktadır.
- 100lm/W'in üzerinde verimlilik.
- Acil aydınlatma kit sistemi uygulanabilir.
- Standart renkler: beyaz, siyah, gri, antrasit koyu gri ve isteğe baęlı özel renk seçenekleri mevcuttur.
- Led trafosu armatürün içine montelidir.
- 5mt uzunluęua kadar opsiyonel çelik sarkıt tel.

Suspension Cord

Ray Sarkıtma Teli



Panos / I02.LL.19612

LED	SMD LED	
Led Power / Led Gücü	21W	
System Power / Sistem Gücü	23W	
Lumen Output from Fixture / Armatür Çıkıř Lümeni CRI>80	2700K	2272
	3000K	2342
	3500K	2390
	4000K	2439
	5000K	2512
Lenght / Uzunluk (A)	X	
Ceiling Cutout Dimension / Tavan Delik Ölçüsü	X	
Mains Switch Dim Option / 220V Anahtar Dim Opsiyonu	✓	
1-10V Dimming Option / 1-10V Dim Seçeneęi	✓	
Dali Dimming Option / Dali Dim Seçeneęi	✓	



*See page 763 for Idt files.
*Iřık eęrileri için sayfa 763 bakınız.